Naświetlacze LED SUPRA II F-30W SMD

MAX-LED lighting technologies

A+

www.max-led.pl



MAX-LED WARRANTY 2 years EXCLUSIVE

ZASTOSOWANIE

- Oświetlenie budynków
- Oświetlenie reklam
- Oświetlenie billboardów
- Oświetlenie parkingów

Dane techniczne podstawowe


Temperatura barwowa	EAN	Strumień świetlny
6000K biała zimna	5903271840649	2420 lm *

Dane techniczne wspólne


Trzonek	-
Moc znamionowa	30 W
Moc odpowiednika	-
Napięcie	175-250 V
Kąt świecenia	160°
Klasa szczelności obudowy	IP65
Współczynnik oddawania barw	Ra ≥ 80
Współczynnik mocy	PF 0,9
Sposób montażu	na zewnątrz
Możliwość ściemniania	NIE
Trwałość	15 000 h
Liczba cykli włączeniowych	20 000
Typ diod LED	SMD
Materiał	aluminium
Kolor obudowy	czarny
Czas rozruchu	<0,2s
Czas rozgrzewania do (60%), do (95%)	<2s

* Całkowity strumień świetlny źródła światła za kloszem przy temp. otoczenia 25°C. Tolerancja strumienia świetlnego +/- 10%.

Rysunek techniczny



Rysunek poglądowy sposób pakowania




Wymiary produktu

X - wymiar	154 [mm]
Y - wymiar	114,4[mm]
Z - wymiar	30,5 [mm]

Opakowanie jednostkowe produktu

ox - wymiar	160 [mm]
oy - wymiar	122 [mm]
oz - wymiar	35 [mm]
Waga	- [gr]

Diagram rozkładu natężenia światła



Opakowanie zbiorcze produktów

Ilość sztuk	30
OX - wymiar	505 [mm]
OY - wymiar	200 [mm]
OZ - wymiar	265 [mm]
Waga	- [kg]

WSZELKIE PRAWA ZASTRZEŻONE 2016 © GRUPA MAROX SP. Z O.O. SP. K.
GRUPA MAROX SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ SPÓŁKA KOMANDYTOWA
POLAND, GOSPODARCZA 24, 32-600 OŚWIĘCIM

Zdjęcia produktów i niektóre parametry techniczne umieszczone w karcie produktu mogą nieznacznie odbiegać od produktów znajdujących się w sprzedaży. Zastrzegamy sobie prawo do błędów w druku.

MAX-LED PRODUCT CARD

LED FLOODLIGHT SUPRA II F-30W SMD



A+

www.max-led.pl

MAX-LED WARRANTY 2 years EXCLUSIVE

APPLICATION

- buildings lighting
- advertising lighting
- bilboard lighting
- parking lighting

Basic technical data


Color temperature	EAN	Luminous flux
6000K cool white	5903271840649	2420 lm *

Common technical data


Base	-
Wattage	30 W
Equivalent	-
Voltage	175-250 V
Beam angle	160°
IP protocol	IP65
Color Rendering Index	Ra ≥ 80
Power factor	PF 0,9
Mounting	outdoor
Dimming	No
Lifespan	15 000 h
Number of switching cycles	20 000
LED type	SMD
Material	aluminum
Housing color	black
Starting time	<0,2s
Warm-up time (60%), do (95%)	<2s

* The total luminous flux of the light source behind the shade at ambient temp. 25 ° C. Tolerance flux +/- 10%.

Technical drawing



Illustrative method of packaging




Product dimensions

X - dimension	150 [mm]
Y - dimension	102 [mm]
Z - dimension	28 [mm]

The unit package of the product

ox - dimension	160 [mm]
oy - dimension	112 [mm]
oz - dimension	50 [mm]
Weight	520 [gr]

Diagram of light intensity distribution



Packaged products

Quantity	30
OX - dimension	530 [mm]
OY - dimension	320 [mm]
OZ - dimension	155 [mm]
Weight	9,9 [kg]

ALL RIGHTS RESERVED 2016 © GRUPA MAROX SP. Z O.O. SP. K.
GRUPA MAROX SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ SPÓŁKA KOMANDYTOWA
POLAND, GOSPODARCZA 24, 32-600 OŚWIĘCIM

THE PICTURES OF PRODUCTS IN THE PRODUCT CARD MAY DIFFER FROM THE ACTUAL PRODUCTS. WE RESERVE THE RIGHT TO PRINTING MISTAKES AND ERRORS. THE SHAPE AND TECHNICAL DATE OF ALL PRODUCTS FROM THIS PRODUCT CARD ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.